

EV-55 DT Electric Industrial Drum Top Vacuums



EV-55 DT Electric Industrial Drum Top Vacuums Published on PrestiVac Inc (https://prestivac.com)





EV-55 DT Electric Industrial Drum Top Vacuums

Published on PrestiVac Inc (https://prestivac.com)



Industrial Vacuums for Hazardous Materials

Industrial Electrical Drum Top Vacuums

PrestiVac Drum Top vacuums are specifically designed to be used on standard 55 gallon drums. The dusts or liquids are collected directly into the standard 55 gallon drum.

Features:

- Powerful Motor High Perfromance
- All Stainless steel construction makes it a solid unit that is easy to clean and sterilize
- Complete with suction hose and accessories
- · Stainless steel industrial cart assembly with ESD safe, conductive wheels

PrestiVac*

EV-55 DT Electric Industrial Drum Top Vacuums

Published on PrestiVac Inc (https://prestivac.com)

- Quiet operation with only xx dB
- Automatic suction shut off system when the collection tank is full of liquids (for Wet & Dry models)
- Stainless steel Drain valve assembly for easy emptying (for Wet & Dry models)

Filtration System:

• Washable, reusable main filter for dust and solids

Applications:

- Debris
- Dust
- Machine shops
- Maintenance/House keeping
- Metal Chips

Specifications:

opeonicatione.			
Model	EV1-55 DT	EV2-55 DT	
Air Watts	561	652	
Electricity	120v / 12a / 1488w	120v / 15a / 1790w	
Air Flow (CFM)	123	202	
Vacuum Pressure (H20)	135	99	
Collection Type	Dry	Dry	
Capacity (gal)	55	55	
dB(A) @ 6 ft			

Included Accessories:

- Suction hose assembly
- · Stainless steel double bend wand assembly
- Floor tool
- Crevice tool
- · Round brush

Optional Accessories:

- Extension wand
- · Single bend wand
- Flat tool
- Wall brush
- Dust extraction Arm

Filtration Options:

HEPA^{Plus*} Filtration with an efficiency of 99.995% @ 0.2 micron. Testing Method: IEST RP-CC034.3. H14. MIL-STD 282 / A.S.T.M. - D2986-91. MPPS method EN 1822.



EV-55 DT Electric Industrial Drum Top Vacuums

Published on PrestiVac Inc (https://prestivac.com)

- **ULPA** Filtration with an efficiency of 99.9995% @ 0.12 micron. Testing Method: IEST RP-CC034.3. H15. MIL-STD 282 / A.S.T.M. D2986-91. MPPS method EN 1822.
- Activated Carbon Filtration System to adsorb and neutralize fumes and vapors

If you have a special application or specific requirement, please feel free to contact us. As manufacturers, we can modify our units to meet your specific needs.

Industrial Vacuums, ELECTRIC