

## **EV1-1 HEPA TT/BP DS HEPA Dustless Sanding Vacuums**





---

## Industrial Vacuums for Hazardous Materials

### Electrical Table Top and Back Pack **HEPA<sup>Plus</sup>** Dustless Sanding Vacuums

PrestiVac Dustless Sanding Vacuums are specifically designed to safely vacuum the hazardous dust generated during surface preparation, coating removal and body repair in the aerospace and automotive industry. Dustless sanding Vacuums minimize contamination issues and increase production quality.

PrestiVac industrial **HEPA<sup>Plus</sup>** vacuums are specifically designed to safely vacuum toxic, nuisance, hazardous dusts. Absolute **HEPA<sup>Plus</sup>** filtration with an efficiency of 99.995% @ 0.2 micron captures all of the hazardous dust and ensures the exhaust air is clean, keeping the operator and the environment safe from exposure and contamination.

Features:

- Powerful Motor - High Performance
- Stainless steel construction makes it a solid unit that is easy to clean and sterilize
- Static dissipating ESD safe
- Complete with static dissipating suction hose, air supply hose and dustless sander
- Compact and lightweight
- Ideal for confined spaces and light applications
- Quiet operation with only xx dB

**Filtration System:**

- 3-stage filtration system for maximum performance and efficiency
- Washable, reusable filters
- Absolute **HEPA<sup>Plus</sup>** Filtration with an efficiency of 99.995% @ 0.2 micron. Testing Method: IEST RP-CC034.3. H14. MIL-STD 282 / A.S.T.M. - D2986-91. MPPS method EN 1822.

**Applications:**

- Aircraft maintenance and repair
- Combustible dusts
- Automotive/Vehicle maintenance and repair
- Ship repair
- Wood products

**Specifications:**

Model	EV1-1 HEPA TT DS	EV1-1 HEPA BP DS
Air Watts	561	561
Electricity	120v / 12a / 1488w	120v / 12a / 1488w
Air Flow (CFM)	123	123
Vacuum Pressure (H2O)	135	135
Collection Type	Dry	Dry
Capacity (gal)	1	1
Dimensions (LxWxH)		
dB(A) @ 6 ft		

**Included Accessories:**

- Suction hose assembly with air hose for dustless sander 25' (3m)
- Vacuum assisted dustless sander

**Optional Accessories:**

- Stainless steel double bend wand assembly
- Floor tool
- Grounding cable
- Dual inlet for (2) operators

**Filtration Options:**

- **ULPA** Filtration with an efficiency of 99.9995% @ 0.12 micron. Testing Method: IEST RP-CC034.3. H15. MIL-STD 282 / A.S.T.M. - D2986-91. MPPS method EN 1822

If you have a special application or specific requirement, please feel free to contact us. As manufacturers, we can modify our units to meet your specific needs.

Dustless Sanding Vacuum Kits, HEPA (ELECTRIC)